

Eve Single Pro Line



PRODUCT DETAILS	
SKU	Variable on configuration
MAX POWER OUTPUT (KW)	3.7 - 22kW
AC/DC	AC
SINGLE/3-PHASE	Both
INPUT POWER LOAD BALANCING	No
IP RATING	IP 55
INTERNAL SAFETY FEATURES	RCD IEC 61851/22 (2017)
FUNCTIONAL SPECIFICATION	
# OF PORTS	1
# OF PORTS TETHERED/UNTETHERED PORTS/CABLE CONNECTION OPTIONS	Type 2 Lead, Type 2 Socket
TETHERED/UNTETHERED PORTS/CABLE	
TETHERED/UNTETHERED PORTS/CABLE CONNECTION OPTIONS	Type 2 Lead, Type 2 Socket
TETHERED/UNTETHERED PORTS/CABLE CONNECTION OPTIONS LCD SCREEN SIZE	Type 2 Lead, Type 2 Socket 3.5"
TETHERED/UNTETHERED PORTS/CABLE CONNECTION OPTIONS LCD SCREEN SIZE CONTACTLESS PAYMENT OPTIONS	Type 2 Lead, Type 2 Socket 3.5" RFID card reader
TETHERED/UNTETHERED PORTS/CABLE CONNECTION OPTIONS LCD SCREEN SIZE CONTACTLESS PAYMENT OPTIONS OVERALL DIMENSIONS	Type 2 Lead, Type 2 Socket 3.5" RFID card reader 370x240x130mm (L,W,D)
TETHERED/UNTETHERED PORTS/CABLE CONNECTION OPTIONS LCD SCREEN SIZE CONTACTLESS PAYMENT OPTIONS OVERALL DIMENSIONS CASING MATERIALS	Type 2 Lead, Type 2 Socket 3.5" RFID card reader 370x240x130mm (L,W,D) Polycarbonate

^{*}The product image shown is for illustration purposes only and may not be an exact representation of the product.