

## **Twin**



PRODUCT DETAILS	
SKU	Variable on configuration
MAX POWER OUTPUT (KW)	3.7 - 22kW
AC/DC	AC
SINGLE/3-PHASE	Both
INPUT POWER LOAD BALANCING	Yes
IP RATING	IP 54
INTERNAL SAFETY FEATURES	RCD IEC 61851-1/22 (2017)
FUNCTIONAL SPECIFICATION	
# OF PORTS	2
# OF PORTS  TETHERED/UNTETHERED PORTS/CABLE CONNECTION OPTIONS	2 Untethered, Type 2 Socket
TETHERED/UNTETHERED PORTS/CABLE	_
TETHERED/UNTETHERED PORTS/CABLE CONNECTION OPTIONS	Untethered, Type 2 Socket
TETHERED/UNTETHERED PORTS/CABLE CONNECTION OPTIONS  LCD SCREEN SIZE	Untethered, Type 2 Socket N/A
TETHERED/UNTETHERED PORTS/CABLE CONNECTION OPTIONS  LCD SCREEN SIZE  CONTACTLESS PAYMENT OPTIONS	Untethered, Type 2 Socket  N/A  RFID card reader
TETHERED/UNTETHERED PORTS/CABLE CONNECTION OPTIONS  LCD SCREEN SIZE  CONTACTLESS PAYMENT OPTIONS  OVERALL DIMENSIONS	Untethered, Type 2 Socket  N/A  RFID card reader  1385x330x200mm (L,W,D)
TETHERED/UNTETHERED PORTS/CABLE CONNECTION OPTIONS  LCD SCREEN SIZE  CONTACTLESS PAYMENT OPTIONS  OVERALL DIMENSIONS  CASING MATERIALS	Untethered, Type 2 Socket  N/A  RFID card reader  1385x330x200mm (L,W,D)  Solid Metal

<sup>\*</sup>The product image shown is for illustration purposes only and may not be an exact representation of the product.